



Product Specifications

Wear Layer	20 mil
Thickness	2mm
Finish / Coating	Exceed™ with Ceramic Micro-Bead
Pattern Repeat	Random Wood Pattern
Edge Treatment	Bevel
Dimensions:	7" x 48"
Standard Adhesive	Commercialon® LVT Adhesive
Backing Class	Commercial Grade
Commercial Traffic	Heavy Commercial

Packaging

Special Technologies

Added Antimicrobial	Yes
----------------------------	-----

Environmental Specifications & Tests

Indoor Air Quality	FloorScore® Certified
LEED v4	Contributes to IAQ: Low Emitting Materials
End of Life	100% Recyclable
Class / ASTM F1700	Class III Printed Film Vinyl Plank - Type B (embossed)
Flooring Radiant Panel	Class 1
ADA Compliance	Compliant For Accessible Routes
ASTM F2055 (Size and Tolerance)	Passes
ASTM F386 (Thickness)	Passes
ASTM F1914 (Residual Indentation)	Passes
ASTM F137 (Flexibility)	Passes
ASTM F2199 (Dimensional Stability)	Passes
ASTM F925 (Chemical Resistance)	Passes
ASTM F1514 (Resistance to Heat)	Passes
ASTM F1515 (Resistance to Light)	Passes
ASTM E648 (Critical Radiant Flux)	Passes
ASTM E662 (Optical Smoke Density)	Passes
ASTM C1028 (Slip Resistance)	Passes
ASTM F970 (Static Load)	Passes

Colorways



0750 Provincial...



0780 Sugar Ma...



0800 Aspen




0820 Rustic Lo...




0830 Weathered ...



0840 Woodland...



0850 Winchester...



0860 Driftwood



4001 Playa



4006 Key Largo



4007 Bay of Ple...