



## Product Specifications

|                           |                                 |
|---------------------------|---------------------------------|
| <b>Wear Layer</b>         | 20 mil                          |
| <b>Thickness</b>          | 2.5mm                           |
| <b>Finish / Coating</b>   | Exceed™ with Ceramic Micro-Bead |
| <b>Pattern Repeat</b>     | Random Wood Pattern             |
| <b>Edge Treatment</b>     | Bevel                           |
| <b>Dimensions:</b>        | 7" x 48"                        |
| <b>Standard Adhesive</b>  | Commercialon® LVT Adhesive      |
| <b>Backing Class</b>      | Commercial Grade                |
| <b>Commercial Traffic</b> | Heavy Commercial                |

## Packaging

## Special Technologies

|                            |     |
|----------------------------|-----|
| <b>Added Antimicrobial</b> | Yes |
|----------------------------|-----|


## Environmental Specifications & Tests

|   |  |
|---|--|
| <b>Indoor Air Quality</b>                 | FloorScore® Certified                      |
| <b>LEED v4</b>                            | Contributes to IAQ: Low Emitting Materials |
| <b>End of Life</b>                        | 100% Recyclable                            |
| <b>Flooring Radiant Panel</b>             | Class 1                                    |
| <b>ADA Compliance</b>                     | Compliant For Accessible Routes            |
| <b>ASTM F2055 (Size and Tolerance)</b>    | Passes                                     |
| <b>ASTM F386 (Thickness)</b>              | Passes                                     |
| <b>ASTM F1914 (Residual Indentation)</b>  | Passes                                     |
| <b>ASTM F137 (Flexibility)</b>            | Passes                                     |
| <b>ASTM F2199 (Dimensional Stability)</b> | Passes                                     |
| <b>ASTM F925 (Chemical Resistance)</b>    | Passes                                     |
| <b>ASTM F1514 (Resistance to Heat)</b>    | Passes                                     |
| <b>ASTM F1515 (Resistance to Light)</b>   | Passes                                     |
| <b>ASTM E648 (Critical Radiant Flux)</b>  | Passes                                     |
| <b>ASTM E662 (Optical Smoke Density)</b>  | Passes                                     |
| <b>ASTM C1028 (Slip Resistance)</b>       | Passes                                     |
| <b>ASTM F970 (Static Load)</b>            | Passes                                     |

## Colorways



4021 Coral Coast




4022 Druidstone



4023 Easter Isl...




4024 Cancun



4025 St. Thomas



4026 Clearwater



4027 Grace Bay



4028 Santa Maria



4029 Whitehav...



4030 Secret La...



4031 Rio



4032 Kyoto