Pentz



Boulevard Plus LVT | P1020 LVT

Product Specifications


| Wear Layer | 20 mil |
|---------------------------------------|--|
| Thickness | 2.5mm |
| Finish / Coating | Exceed™ with Ceramic Micro-Bead |
| Pattern Repeat | Random Wood Pattern |
| Edge Treatment | Bevel |
| Dimensions: | 7" x 48" |
| Standard Adhesive | Commercialon® LVT Adhesive |
| Backing Class | Commercial Grade |
| Commercial Traffic | Heavy Commercial |
| Packaging | |
| Special Technologies | |
| Added Antimicrobial | Yes |
| Environmental Specifications & Tests | |
| Indoor Air Quality | FloorScore® Certified |
| LEED v4 | Contributes to IAQ: Low Emitting Materials |
| End of Life | 100% Recyclable |
| Flooring Radiant Panel | Class 1 |
| ADA Compliance | Compliant For Accessible Routes |
| ASTM F2055 (Size and Tolera | rance) Passes |
| ASTM F386 (Thickness) | Passes |
| ASTM F1914 (Residual Indentation) | Passes |
| ASTM F137 (Flexibility) | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resist | tance) Passes |
| ASTM F1514 (Resistance to H | Heat) Passes |
| ASTM F1515 (Resistance to L | Light) Passes |
| ASTM E648 (Critical Radiant | t Flux) Passes |
| ASTM E662 (Optical Smoke Density) | Passes |
| ASTM C1028 (Slip Resistance | e) Passes |
| ASTM F970 (Static Load) | Passes |
| | |

Colorways




4027 Grace Bay







4028 Santa Maria 4029 Whitehav...









4030 Secret La... 4031 Rio

QUICKSHIP 4026 Clearwater



4032 Kyoto