



Product Specifications

| | |
|----------------------------|---|
| Construction | Level Loop |
| Backing | Woven Polypropylene |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Nylon |
| Face Weight | 26 oz./sy (882 grams/m ²) |
| Pile Density | 6933 oz./y ³ (257.08 kg/m ³) |
| Pattern Repeat | 24.00" (w) x 36.00" (l) approx. (60.96cm x 91.44cm) |
| Gauge | 1/10 (3.94 rows/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Standard Back Encore SD Fiber |
| Optional Warranties | iLoc® Backing |

Special Technologies

Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | N/A Certified |
| Total Recycled Content | 0% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways

| | | | | | |
|---|---|---|---|---|--|
|  2641 Loyal |  2642 Nobel |  2643 Courteous |  2644 Honor |  2645 Character |  2646 Thoughtful |
|  2647 Faithful |  2648 Romantic |  2649 Defender |  2650 Truthful |  2651 Humility |  2652 Respectful |
|  2653 Justice |  2654 Gentleman |  2655 Generous |  2656 Humanity | | |