



Product Specifications


| | |
|----------------------------|---|
| Construction | Textured Loop |
| Backing | Woven Polypropylene |
| Dye Method | Solution Dyed |
| Fiber Type | Encore® SD Nylon |
| Face Weight | 26 oz./sy (882 grams/m ²) |
| Pile Density | 7127 oz./y ³ (264.27 kg/m ³) |
| Pattern Repeat | 24.00" (w) x 36.00" (l) approx. (60.96cm x 91.44cm) |
| Gauge | 1/10 (3.94 rows/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Standard Back Encore SD Fiber |
| Optional Warranties | iLoc® Backing |

Special Technologies


Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | N/A Certified |
| Total Recycled Content | 0% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 3 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |

Colorways



2040 Offbeat



2041 Unique




2042 Discrete




2043 Muddled




2044 Varied




2045 Contrary




2046 Novel



2047 Jumbled




2048 Mingled



2049 Composite



2050 Bizarre



2051 Distinct