



Product Specifications


Construction	Textured Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon
Face Weight	26 oz./sy (882 grams/m ²)
Pile Density	7127 oz./y ³ (264.27 kg/m ³)
Pattern Repeat	24.00" (w) x 36.00" (l) approx. (60.96cm x 91.44cm)
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back Encore SD Fiber
Optional Warranties	iLoc® Backing

Special Technologies


Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



2040 Offbeat



2041 Unique




2042 Discrete



2043 Muddled




2044 Varied




2045 Contrary




2046 Novel



2047 Jumbled




2048 Mingled



2049 Composite



2050 Bizarre



2051 Distinct