



Product Specifications

Construction	Textured Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon
Face Weight	20 oz./sy (678 grams/m2)
Pile Density	7165 oz./y3 (265.68 kg/m3)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Encore SD Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	40.71%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Quarter Turn, Monolithic, Ashlar

Colorways

 2040 Offbeat	 2041 Unique	 2042 Discrete	 2043 Muddled	 2044 Varied	 2045 Contrary
 2046 Novel	 2047 Jumbled	 2048 Mingled	 2049 Composite	 2050 Bizarre	 2051 Distinct