



Product Specifications

Construction	Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	18 oz./sy (610 grams/m2)
Pile Density	6416 oz./y3 (237.91 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Size	12" x 48" approx. (30.48cm x 121.92cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT APEX® SDP Polyester Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs


Special Technologies

Environmental Specifications & Tests


NSF 140:	Gold Certified
Total Recycled Content	41.8%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Herringbone, Ashlar


Colorways




3135 Indigo




3136 Royal Pur...




3137 Midnight




3138 Chili Red



3139 Crimson




3140 Carob




3141 Matte Lake




3142 Sunburst




3143 Medallion




3144 Cyber




3145 Ocean Tro..



3146 Cloud



3147 Parrot



3171 Skyrocket