



Product Specifications

Construction	Cut and Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	20 oz./sy (678 grams/m2)
Pile Density	6545 oz./y3 (242.69 kg/m3)
Pattern Repeat	24.00" (w) x 36.00" (I) approx. (60.96cm x 91.44cm)
Gauge	1/12 (4.72 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back APEX® SDP Polyester Fiber
Optional Warranties	iLoc® Backing
Special Technologies	

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less then 450 flaming (ASTM E 662)
Static Test	Less then 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways



3388 Certainty





3389 Matter of ...



3394 All Sewn Up 3395 Sure Bet



3390 Cold Hard ...



3396 Shoo-In



3391 Done Deal



3392 Fact of Life 3393 Sure Thing

