



Product Specifications


| | |
|----------------------------|--|
| Construction | Patterned Loop |
| Backing | Woven Polypropylene |
| Dye Method | Solution Dyed |
| Fiber Type | APEX SDP® Polyester |
| Face Weight | 20 oz./sy (678 grams/m ²) |
| Pile Density | 6691 oz./y ³ (248.11 kg/m ³) |
| Pattern Repeat | 24.00" (w) x 26.50" (l) approx. (60.96cm x 67.31cm) |
| Gauge | 1/12 (4.72 rows/cm) |
| Standard Width | 12 ft 3.66 m |
| Standard Adhesive | Commercialon Premium Carpet Adhesive |
| Standard Warranties | Standard Back APEX® SDP Polyester Fiber |
| Optional Warranties | iLoc® Backing |

Special Technologies


Environmental Specifications & Tests

| | |
|-------------------------------|------------------------------------|
| NSF 140: | N/A Certified |
| Total Recycled Content | 0% |
| Flooring Radiant Panel | Class 1 |
| Smoke Density | Less than 450 flaming (ASTM E 662) |
| Static Test | Less than 4 kv (AATCC-134) |
| ADA Compliance | Compliant For Accessible Routes |
| Pill Test | Yes |
| Lightfastness | Yes |


Colorways



3534 Redirect




3535 Domain




3536 Filter




3537 Search




3538 Hosting




3539 Image Ov...



3540 Wireframe



3541 Meta Tag



3542 Cookies