



Product Specifications

Construction	Patterned Loop
Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	APEX SDP® Polyester
Face Weight	16 oz./sy (543 grams/m2)
Pile Density	7243 oz./y3 (268.58 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Size	12" x 48" approx. (30.48cm x 121.92cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT APEX® SDP Polyester Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs

Special Technologies

Environmental Specifications & Tests

NSF 140:	Gold Certified
Total Recycled Content	75.3%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Herringbone, Ashlar

Colorways

 3135 Indigo	 3136 Royal Purple	 3137 Midnight	 3138 Chili Red	 3139 Crimson	 3140 Carob
 3141 Matte Lake	 3142 Sunburst	 3143 Medallion	 3144 Cyber	 3145 Ocean Troop	 3146 Cloud
 3147 Parrot					