



## Product Specifications


<b>Construction</b>	Patterned Loop
<b>Backing</b>	Woven Polypropylene
<b>Dye Method</b>	Solution Dyed
<b>Fiber Type</b>	APEX SDP® Polyester
<b>Face Weight</b>	20 oz./sy (678 grams/m <sup>2</sup> )
<b>Pile Density</b>	6396 oz./y <sup>3</sup> (237.17 kg/m <sup>3</sup> )
<b>Pattern Repeat</b>	72.00" (w) x 30.00" (l) approx. (182.88cm x 76.20cm)
<b>Gauge</b>	1/12 (4.72 rows/cm)
<b>Standard Width</b>	12 ft 3.66 m
<b>Standard Adhesive</b>	Commercialon Premium Carpet Adhesive
<b>Standard Warranties</b>	<b>Standard Back</b> <b>APEX® SDP Polyester Fiber</b>
<b>Optional Warranties</b>	<b>iLoc® Backing</b>

## Special Technologies


## Environmental Specifications & Tests

<b>NSF 140:</b>	N/A Certified
<b>Total Recycled Content</b>	0%
<b>Flooring Radiant Panel</b>	Class 1
<b>Smoke Density</b>	Less than 450 flaming (ASTM E 662)
<b>Static Test</b>	Less than 4 kv (AATCC-134)
<b>ADA Compliance</b>	Compliant For Accessible Routes
<b>Pill Test</b>	Yes
<b>Lightfastness</b>	Yes


## Colorways




2759 Gray




2760 Spring



2761 Dust




2762 Camelback




2763 Mine




2764 Caravan



2765 Paint



2766 Sky



2767 Obsidian