



Product Specifications

Construction	Textured Loop
Backing	Woven Polypropylene
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon
Face Weight	26 oz./sy (882 grams/m ²)
Pile Density	6600 oz./y ³ (244.73 kg/m ³)
Pattern Repeat	N/A
Gauge	1/10 (3.94 rows/cm)
Standard Width	12 ft 3.66 m
Standard Adhesive	Commercialon Premium Carpet Adhesive
Standard Warranties	Standard Back Encore SD Fiber
Optional Warranties	iLoc® Backing

Special Technologies

Environmental Specifications & Tests

NSF 140:	N/A Certified
Total Recycled Content	0%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 4 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Colorways

 2934 High Defini...	 2935 4K	 2936 Adaptive	 2937 Wi-Fi	 2938 Html	 2939 Graphics
 2940 Buffering	 2941 Firewall	 2942 Bandwidth	 2944 Aspect	 2945 Latency	 2946 Encoding