



**Product Specifications**

|                            |   |
|----------------------------|---|
| <b>Construction</b>        | Patterned Loop  |
| <b>Backing</b>             | Nexus® Modular  |
| <b>Dye Method</b>          | Solution Dyed   |
| <b>Fiber Type</b>          | Encore® SD Nylon  |
| <b>Face Weight</b>         | 15 oz./sy (509 grams/m2)  |
| <b>Pile Density</b>        | 6300 oz./y3 (233.61 kg/m3)  |
| <b>Pattern Repeat</b>      | N/A   |
| <b>Gauge</b>               | 1/12 (4.72 rows/cm)   |
| <b>Standard Size</b>       | 12" x 48" approx. (30.48cm x 121.92cm)  |
| <b>Standard Adhesive</b>   | Commercialon Premium Modular Adhesive   |
| <b>Optional Adhesive</b>   | TileTabs  |
| <b>Standard Warranties</b> | <b>Nexus Modular<br/>Commercialon Adhesive for Modular<br/>Carpet &amp; LVT<br/>Encore SD Fiber</b> |
| <b>Optional Warranties</b> | <b>Commercialon High Moisture Adhesive<br/>for Modular Carpet and LVT<br/>Tile Tabs</b>             |


**Special Technologies**

**Environmental Specifications & Tests**


|                               |                                    |
|-------------------------------|------------------------------------|
| <b>NSF 140:</b>               | Gold Certified                     |
| <b>Total Recycled Content</b> | 76.4%                              |
| <b>Flooring Radiant Panel</b> | Class 1                            |
| <b>Smoke Density</b>          | Less than 450 flaming (ASTM E 662) |
| <b>Static Test</b>            | Less than 4 kv (AATCC-134)         |
| <b>ADA Compliance</b>         | Compliant For Accessible Routes    |
| <b>Pill Test</b>              | Yes                                |
| <b>Lightfastness</b>          | Yes                                |

**Installation Methods:** Herringbone, Ashlar


Colorways




3052 Ecliptic




3053 Zodiac




3054 Galaxy



3055 Aurora



3056 Celestial



3057 Juno