



Product Specifications

Backing	Nexus® Modular
Dye Method	Solution Dyed
Fiber Type	Encore® SD Nylon
Face Weight	15 oz./sy (509 grams/m2)
Pile Density	6300 oz./y3 (233.61 kg/m3)
Pattern Repeat	N/A
Gauge	1/12 (4.72 rows/cm)
Standard Size	24" x 24" approx. (60.96cm x 60.96cm)
Standard Adhesive	Commercialon Premium Modular Adhesive
Optional Adhesive	TileTabs
Standard Warranties	Nexus Modular Commercialon Adhesive for Modular Carpet & LVT Encore SD Fiber
Optional Warranties	Commercialon High Moisture Adhesive for Modular Carpet and LVT Tile Tabs


Special Technologies

Environmental Specifications & Tests


NSF 140:	Gold Certified
Total Recycled Content	43.54%
Flooring Radiant Panel	Class 1
Smoke Density	Less than 450 flaming (ASTM E 662)
Static Test	Less than 3 kv (AATCC-134)
ADA Compliance	Compliant For Accessible Routes
Pill Test	Yes
Lightfastness	Yes

Installation Methods: Brick, Quarter Turn, Monolithic, Ashlar


Colorways




3052 Ecliptic




3053 Zodiac




3054 Galaxy




3055 Aurora




3056 Celestial




3057 Juno




3058 Ceres



3059 Nadir



3060 Zenith



3061 Cosmic